



Greyback Bubble Free Film

Greyback Bubble Free Film

grimco.ca

Briteline Bubble Free is a 3 mil polymeric PVC film, greyback permanent or removable bubble free adhesive. Especially developed for solvent, eco-solvent, latex and UV printing methods.

Applications

Recommended for a wide range of short and medium term promotional applications on flat or slightly curved surfaces. Use where an air egress adhesive is beneficial.

Thickness

3 mil

Temperature Range

Application Temperature: (°C) > 5
Service Temperature: (°C) -40 to 80

Storage Stability

2 year shelf life when stored at
20° C and 50% relative humidity

Country of Origin

Portugal

Recommendations

Flat and slightly curved applications. Latex printing should not exceed a maximum temperature of 105°C. For best quality print, use the correct printing profiles.

Adhesion

Peel Adhesion Steel: 20 min (N/25mm) >10
Peel Adhesion Steel: 24 h (N/25mm) >17

Expected Durability

5-7 years vertical exposure under
normal conditions

Available Size

54" X 50YD

Available Finishes

Gloss
Matte

Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions or sale, including disclaimer of warranties and limitation of liability.