



High Tack Bubble Free Film

High Tack Bubble Free Film

grimco.ca

Briteline High Tack Bubble Free is a 3 mil high opacity polymeric PVC film with a high tack permanent bubble free adhesive and clay coated double PE embossed liner.

Applications

Recommended for a wide range of short term promotional applications on flat surfaces.
Good adhesion to low energy surfaces with the bubble free adhesive for easier installation.

Thickness

3 mil

Temperature Range

Application Temperature (°C) >5
Service Temperature (°C) -40 to 80

Storage Stability

2 year shelf life when stored between 20° C and 50% relative humidity

Country of Origin

Portugal

Recommendations

Flat and Slightly curved surfaces. Flat surface applications. Latex printing should not exceed a maximum temperature of 105°C. For best quality print, use the correct printing profiles. NOT recommended for floor graphics; unclean, rough or flexible surface.

Adhesion

Peel Adhesion Steel: 20 min (N/25mm) >11
Peel Adhesion Steel: 24 h (N/25mm) >28

Expected Durability

5-7 years vertical exposure
under normal conditions

Available Sizes

54" X 50YD

Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions of sale, including disclaimer of warranties and limitation of liability.