



## UV Overlamine Film

[grimco.ca](http://grimco.ca)

Briteline UV Overlamine is a pressure sensitive 2.75mil PVC film offering resistance to UV degradation with a permanent acrylic adhesive. This laminate protects the graphics from abrasion, moisture, and ultraviolet radiation without any milky or silvering effect. Can be used as anti-graffiti protection.

### Applications

This overlamine is designed to protect digital and screen printed images. Can be used in most instances on a flat surface where an overlay is required on interior or exterior.

### Thickness

2.75 mil

### Temperature Range

Application Temperature (°C) >10  
Service Temperature (°C) -40 to 80

### Storage Stability

2 year shelf life when stored at  
20° C and 50% relative humidity

### Country of Origin

Portugal

### Recommendations

Printed materials must be properly dried before applying the lamination. It is recommended the film remains at least 24 hours at the temperature of the workplace before it is used.

### Adhesion

Peel Adhesion Steel: 20 min (N/25mm) >15  
Peel Adhesion Steel: 24 h (N/25mm) >22

### Expected Durability

Up to 4 years vertical exposure under  
normal conditions

### Available Sizes

54" X 50YD  
63" X 50YD

### Available Finishes

Gloss  
Luster  
Matte

#### Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions or sale, including disclaimer of warranties and limitation of liability.